

T350 Specifications

Platform Size	30 x 48" / 0.76 x 1.22 m
Overall Width	4' 9" / 1.44 m
Outrigger Footprint-Length	11' 6" / 3.51 m
Outrigger Footprint-Width	10' 5" / 3.18 m
Stowed Height	6' 6" / 1.98 m
Stowed Length	21' 4" / 6.5 m
Ground Clearance	14" / 36 cm
Entry Height-extended	10" / 25 cm
Leveling Capability	11°
Weight	3,400 lb / 1,542 kg
Max. Ground Bearing Pressure	23 psi / 1.62 kg/cm ²

Towing Speed Rating	65 mph / 105 kmph
Tongue Weight	242 lb / 110 kg
Brakes	Hydraulic Surge
Parking Brakes	Std.
Tire Size	205/75 R14
Tire Type	Pneumatic

DC Power	24V DC
Batteries	4 x 6V, 220 amp-hr
Gasoline Engine (Optional)	Honda GX 270-9 hp
Fuel Tank Capacity (Optional)	1.6 gal. / 6.1 L
Hydraulic Reservoir	4.0 gal. / 15.14 L

Platform Height	35' / 10.67 m
Horizontal Outreach	
Horizontal Outreach - Working Outreach	20' 2" / 6.15 m
Horizontal Outreach - Centerline to Platform Edge	18' 8" / 5.69 m
Horizontal Outreach - From Outrigger Pad Edge	13' 6" / 4.11 m
Up and Over Height	15' / 4.57 m
Swing	410° Non-Continuous
Platform Capacity	
Platform Capacity - Standard Platform	500 lb / 227 kg
Platform Capacity - Optional Platform Rotator	440 lb / 200 kg
Material Hook Capacity	500 lb / 227 kg
Platform Rotator (Optional)	90° Manual
Jib	
Jib - Length	n/a
Jib - Vertical Motion	n/a